

TNP-100

IP Multiplexer / De-multiplexer



Standards based Telemetry & IRIG over Packet network
 Low latency transmission over IP networks
 Four user programmable multi-function IO ports
 Enables TMOIP, T1/E1, Video & AES/EBU Audio over IP
 Enables Analog & Digital data acquisition services
 Superior Flat Line response Integrated Bit-Sync, BERT, and Monitoring capabilities
 Managed via Embedded Web Server and SNMP.

High performance, low latency leader

IPtec specialises in facilitating high performance, low latency services over packet based networks. IPtec provides reliable, high quality products for low latency, Telemetry (TMOIP), E1/T1 (CESoIP), video and data acquisition services. These products enable transport of high quality telemetry, IRIG, voice (E1/T1), and Video signals over Ethernet, IP-based or MPLS networks.

Overview

The IPtec TNP-100 IP Multiplexer/De-multiplexer and IP Protocol Adaptor transports serial Telemetry data, professional AES/EBU Audio and associated IRIG signals between locations linked by commercial IP-based networks with the highest degree of signal integrity. The TNP-100 Flat Line Response (FLR) and adaptive IP packet size technology enables ultra-low latency transmission and superior Time-Data Correlation (TDC), while preserving the original signal integrity. The TNP-100 supports aggregate data rates up to 1 Gbps and performs QoS support enabling IP networks to provide reliable and cost effective data delivery from the source to multiple destinations.

Applications

As the proliferation of IP network technology continues from the desktop through the Access network, and to the network backbone; it is desired to take advantage of the "port to port" connectivity, low cost, and general availability of these networks to transport legacy "timing sensitive services". These technology advances enable telemetry collection, processing centres, control centres, ground stations, test sites, and payload operations facilities to migrate from expensive dedicated serial interconnections to commercially available IP networks. Multiple telemetry streams often need to be transmitted from one point to another over large distances while maintaining their time-data relationship. The TNP-100 enables IP networks to perform bi-directional "real-time" transmission of time correlated signals. The TNP-100 performs protocol translation between custom serial signaling used by legacy, modern TMOIP telemetry equipment, and the standards-based IP network protocol. The TNP-100 recovers the original serial signaling at the destination with the highest performance possible allowing the TNP-100 to be a drop-in replacement for existing serial transport systems. The TNP-100 offers TMOIP compliant transparent transmission of telemetry and IRIG over IP LAN and WAN networks.

IP Multicast technology enables the TNP-100 to transmit Serial telemetry and IRIG signals between a source (local or remote) and one or more destinations. The TNP-100 innovative adaptive clock recovery and buffer management algorithms are designed to recover PCM telemetry clocking information and maintain specific system latency for the streaming service set by the user, which is independent of the streaming data rate and thus enabling a “Flat-line response” between services over IP network infrastructures. The TNP-100 even suppresses or removes jitter from the applied telemetry streams before reaching the destination and produces accurate serial output at each destination. The TNP-100 efficiently performs conversion to and from IP packets, relying on Field-Programmable Gate Array (FPGA) technology running software-defined algorithms to provide speed and configurability. IPtec’s software is included allowing dynamic and/or static configuration and monitoring of the distribution network via Graphical User Interfaces or secure SNMP connections.

TNP-100 Telemetry Application Design

The TNP-100 is a standards compliant network processor enabling transparent, low latency, bidirectional transfer of almost any type of digital and analog signals over Ethernet, IP-enabled, and MPLS networks. The TNP-100 is a single board platform enabling Ethernet (LAN), Circuit Emulation (CESoIP), Video, AES/EBU Audio, PCM Telemetry (TMoIP, SCADA), and Analog Data acquisition service solutions. Flexible, multi-function interfaces enable the network processor without physical re-configuration to be used in many different applications, where high performance and ultra-low latency are required. The TNP-100 Flat Line Response System is capable of providing transmission of IRIG timing signals along with the telemetry data and other services and maintains time correlation between the services, while achieving the shortest end to end transmission latency. The TNP-100 single board platform comprises of a Host running a real-time Linux operating system, a manage Ethernet Switch with multiple Gb Ethernet ports, and programmable multi-functional I/O interfaces (service ports).

The service ports can be configured to operate as inputs or outputs and support most digital and analog electrical signal formats without any hardware changes to the system. The four service port TNP-100 unit is available in 1RU, ½-width 19” consuming typ. 12 W of power. Two TNP-100 units provide an 8 service port system that fits in a 19” 1RU rack space. Systems with very large numbers of services ports are easily realised by directly interconnecting as many as required TNP-100 units for multiplexing/De-multiplexing (service aggregation) of streams/services only limited by the 1Gbps standard network bandwidth per TNP-100 Cluster. Each multi-function I/O interfaces supports up to 50Mb/s TTL, ECL, and most other digital electrical signal formats as well as Video and Analog signal formats without any hardware change, significantly improving CapEx and OpEX. The design of the TNP-100 and the IPtec software architecture permits easy tailoring of a standard TNP-100 configuration to meet customer specific requirements.

Technical Specification

Multi-Function Interface

Number of user configurable inputs/outputs
4 multi-service ports

Connector

BNC

- Impedance: 75 ohms (Unbalanced)

Telecom

E1,T1 (CESoIP) (PWE3)

Connector: BNC & RJ45 (with optional in-line Balun adaptor)

Impedance: 75 ohms (Unbalanced), 110 ohms (Balanced)

Digital Data Acquisition Format Support (TMoIP)

TTL, ECL, CML & Automatic Threshold detection

- Impedance: 50 ohms and 75 ohms
- Data Rate: 80b/s to 50Mb/s per port
- Bit-Sync: 1000b/s to 22Mb/s (NRZ Data format)

IRIG Timing

Analog format (1, 10 & 100KHz)

Signal Level

- Input: 0.2Vpp min. 10Vpp max
- Output: 3Vpp (50 ohms), 10Vpp (25 ohms)
- Impedance
- Input: Hi-Z, 600 ohms and 50 ohms
- Output: 25, 50 & 600 ohms

Analog Data Acquisition & Video

Baseband Analog signals

- Signal Level: 5Vpp max
- Impedance: 50 ohms and 75 ohms
- Bandwidth: Up to 10Mhz
- Video data rates: 10Mb/s-400Mb/s (user configurable)
- Video Processing Latency: 2mS to 10mS

Signal Processing

- Processing Latency <2mS
- PDV Compensation: 2mS to 4S
- Packet Size: up to 1463 bytes

Professional AES/EBU Audio

Unbalanced AES/EBU Audio bi-phase encoded signal by use of built-in Bit-Sync

Remote Management

Built-in Web-based GUI and SNMPv2 and v3

Ethernet Service Ports & Network Interface

One pluggable SFP module. 1000Base-X

Two RJ45. 10/100/1000Base-T

Maintenance

An onboard BERT (Bit Error Rate Test) generator allows remote testing. Following test patterns are supported:

- Alternating Ones and Zeroes
- Pseudorandom 223-1
- Pseudorandom 215-1

Physical Dimensions

1RU, ½-width 19”. Two units fit in a 19” 1RU rack space (H x W x D) 1.77” x 8.50” x 12.00” / 4.5cm x 22,0cm x 30.5cm

Environmental Conditions

Operating Temperature: 0 to 50°C (32F to 122F)

Storage Temperature: -40 to 70°C (-40F to 158F)

Relative Humidity: 5% to 90% (Non Condensing)

Relevant Publications

FCC CFR47 Part15B Class A

UL/IEC 60950-1, CE Certified

Telemetry over IP (TMoIP), RCC Standard 218-07

IETF-PWE3, SAToIP, CESoIP, G823/G.824, IEEE

808.1D, 1Q, 1P, 1p, 1ag, 3x, 1x, 2, 3ad,

3u, 3z, 3ah, IRIG 106, IRIG A/B/D/H/G

Power

100 – 240V AC (47 – 63Hz) , < 20W